

LIGHT SOURCE

All published luminaire photometric testing performed to IESNA LM-79-08 standards by a NVLAP accredited laboratory. Data is considered to be representative of the configurations shown, within the tolerances allowed by Lighting Facts. To obtain an IES file specific to your project, please contact the factory.

| OPTION | WATTAGE | LUMENS <small>*Avg. value, actual value dependent on bulb used</small> | CRI | VOLTAGE | DIMMING |
|-------------------------------|---------|---|------|---------|----------------|
| INCANDESCENT (MED E26) | | | | | |
| E26 | 60W Max | 800* | 100* | 120 VAC | Bulb Dependant |

SPECIFICATIONS

CERTIFICATIONS, LISTINGS & WARRANTY

MADE IN THE USA
 Manufactured and Hand-Crafted in Our 60,000 Square Foot Facility
 Located in Titusville, FL

CSA LISTED FOR DRY LOCATIONS

LIMITED WARRANTY
 For Additional Information on Our Limited Warranty, Please See
 Our Terms & Conditions

DESIGN

MOUNTING STEM
 Crafted from 1/8" Diameter Aluminum Tubing

POWDER COAT FINISHES
 Polyester Powder Coat Finishes Are Electro-Statically Applied and
 Thermocured