REV 08.08.19
AERO SHALLOW BOWL STEM MOUNT LIGHT
BARN LIGHT QUICK SHIP COLLECTION
Max Weight: 10.0 lbs

PROJECT NAME _____

PROJECT TYPE _____

SPS–0339

BLE - QS - S - _____ - _____ - _____ - _____ - _____
              A   B   C   D   E

Order Example: BLE - QS - S - SBA12 - 975 - ST718 - SC - WC

A – SHADE SIZE
SBA12	12" Aero Shade
SBA16	16" Aero Shade

B – FINISHES
POWDER COAT FINISHES[1]:
100	Black
200	White
300	Dark Green
975	Galvanized

C – MOUNTING OPTIONS
STEM MOUNT OPTIONS:
ST706	.75" Stem Mount, 6"
ST712	.75" Stem Mount, 12"
ST718	.75" Stem Mount, 18"
ST724	.75" Stem Mount, 24"

D – CANOPY
SC	Standard Canopy
HSC	Hang Straight Canopy

E – WIRE CAGE
NA	None/No Wire Cage
WC	Wire Cage[2]

IMPORTANT: *(1) All Powder Coat finished shades, Galvanized excluded, feature a white interior (2) If selected, wire cage finish will match selection in Section B*

DIMENSIONAL DRAWING

4.3"   0.8"

VARIES

A

B

SHADE CODE	HEIGHT (A)	DIAMETER (B)
SBA12	6.25"	12"
SBA16	7.75"	16"

LIGHT SOURCE

All published luminaire photometric testing performed to IESNA LM-79-08 standards by a NVLAP accredited laboratory. Data is considered to be representative of the configurations shown, within the tolerances allowed by Lighting Facts. To obtain an IES file specific to your project, please contact the factory.

OPTION	WATTAGE	LUMENS *Avg. value, actual value dependent on bulb used*	CRI	VOLTAGE	DIMMING
INCANDESCENT (MED E26)					
E26	200W Max	*3000	*100	120 VAC	Bulb Dependant

Address: 320 Knox McRae Drive Titusville, FL 32780   Phone: (800) 407-8784   Email: sales@barnlight.com   Website: www.barnlight.com

1

SPECIFICATIONS

CERTIFICATIONS, LISTINGS & WARRANTY

MADE IN THE USA
Manufactured and Hand-Crafted in Our 60,000 Square Foot Facility Located in Titusville, FL

CSA LISTED FOR WET LOCATIONS

LIMITED WARRANTY
For Additional Information on Our Limited Warranty, Please See Our Terms & Conditions

DESIGN

AERO SHALLOW BOWL SHADE
Hand-Spun from High Purity 0.050" Thick 3003-O Temper Aluminum

POWDER COAT FINISHES
Polyester Powder Coat Finishes Are Electro-Statically Applied and Thermocured

STEM
3/4" Nominal (1.05" Actual) Sch 40, 6063 Aluminum Mounting Stem. Custom Lengths Available upon Request.