

LIGHT SOURCE

All published luminaire photometric testing performed to IESNA LM-79-08 standards by a NVLAP accredited laboratory. Data is considered to be representative of the configurations shown, within the tolerances allowed by Lighting Facts. To obtain an IES file specific to your project, please contact the factory.

OPTION	WATTAGE	VOLTAGE	LUMENS	DIMMING
INCANDESCENT				
CANDELABRA TYPE A, B, BA	25W	120V	N/A	N/A

SPECIFICATIONS

CERTIFICATIONS, LISTINGS & WARRANTY

MADE IN THE USA
 Manufactured and Hand-Crafted in Our 60,000 Square Foot Facility
 Located in Titusville, FL

CSA LISTED FOR DRY LOCATIONS

LIMITED WARRANTY
 For Additional Information on Our Limited Warranty, Please See
 Our Terms & Conditions

DESIGN & FINISHES

WALL SCONCE SHADE
 If Powder Coat Finish Selected, Shade is Hand-Spun from High Purity 0.050" Thick 3003-O Temper Aluminum. If Porcelain Finish Selected, Shade is Hand-Spun from 20 Guage Sheet Metal.

POWDER COAT FINISHES
 Polyester Powder Coat Finishes Are Electro-Statically Applied and Thermocured

PORCELAIN FINISHES
 Applied by Hand and Fired in a High Temperature Oven

ADJUSTABLE HEAD
 Swivels up to 90 Degrees