



INSTALLATION INSTRUCTIONS PLUG-IN WALL SCONCE

Thank you for purchasing from Barn Light Electric, America's leading manufacturer of hand-crafted shades and exclusive source for porcelain enamel lighting! For questions or concerns about your purchase, please contact us!


INS-0038 REV A (HWK-0044)

ALTERNATE FIXTURE DRAWINGS

This fixture can also be installed as an upright, illuminating ceilings or signs above.



Front View



Side View

IMPORTANT

Read all instructions before assembly. Installation is to be done by a qualified professional.

CAUTION: Risk of fire, this product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.

INSTRUCTIONS

NOTE: Mount light within reach of outlet; use of extension cord is not recommended.

1. Loosen thumb screw (A) to allow for the adjustment of the stem (B) during installation. Retighten to lock in place.
2. Loosen the collar (C) (located at the end of the stem [B]) and carefully slide both the collar (C) and coverplate (D) onto the stem (B). **NOTE: Be careful not to scratch the paint when sliding these parts.**
3. Thread nut (E) and crossbar (F) onto stem (B). Use nut (E) to lock the crossbar (F) into place.
4. Mount crossbar (F) to wall with the two screws (G) and plastic anchors (H) (if needed).
5. Slide the coverplate (D) until flush against the wall. **NOTE: Guide the cord out through the bottom notch in the coverplate (D).**
6. Slide collar (C) against the coverplate (D) and tighten set-screw (I) to lock in place.

PLUG-IN WALL SCONCE

- A. Thumb
- B. Stem
- C. Collar
- D. Coverplate
- E. Nut
- F. Crossbar
- G. Mounting Screws
- H. Wall Anchors
- I. Set Screw

