

INSTALLATION INSTRUCTIONS

DOWNTOWN MINIMALIST PLUG-IN WALL SCONCE

Thank you for purchasing from Barn Light Electric, America's leading manufacturer of hand-crafted shades and exclusive source for porcelain enamel lighting! For questions or concerns about your purchase, please contact us!

INS-0040 REV A (HWK-0045)

ALTERNATE FIXTURES

These alternative fixtures follow the same installation instructions as the illustration shown below.





The Downtown Minimalist Adjustable Plug-In Sconce The Downtown Swing Arm Plug-In Sconce

IMPORTANT

Read all instructions before assembly. Installation is to be done by a qualified professional.

CAUTION: Risk of fire, this product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.

INSTRUCTIONS

NOTE: Mount light within reach of outlet; use of extension cord is not recommended.

- 1. Thread both screws (A) all the way into the two holes of the swivel crossbar (B) that align with the two holes in the coverplate (C). NOTE: Thread screws (A) through in the direction shown in the drawing.
- 2. Secure the swivel crossbar (B) to wall with the two mounting screws (D) included. NOTE: Use plastic anchors (E) if installing in a hollow wall or concrete. Flatplate of swivel crossbar (B) must be flush against wall.
- 3. Place fixture (F) over swivel crossbar (B) and install both lock-up nuts (G) onto the protruding machine screws (A). Tighten lock-up nuts (G) until fixture (F) is secure. NOTE: Guide the cord out through the bottom notch in the coverplate (C).

