



**MOUNTING OPTIONS:**

FLUSH MOUNT



- Allows fixtures to be flush with the ceiling
- Preferred mounting option for tight spaces such as closets, bathrooms and hallways or areas with shallow ceilings
- Ceiling canopy dimensions: 4.25" diameter x 1" projection

STEM MOUNT



- Customers can choose between two different stem diameters: 1/2 inch and 3/4 inch
- Six stem lengths are available: 6", 12", 18", 24", 36" and 48"
- Custom stem lengths are available per customer request
- Ceiling canopy dimensions: 4.25" diameter x 1" projection

CHAIN HUNG



- Customers can choose from four chain lengths: 3 ft. (standard), 4 ft., 5 ft. and 6 ft.
- Chain links are available in 12 varying colors
- Interlinking cord is available in 13 different styles allowing for customization of cord/chain combination
- Ceiling canopy dimensions: 4.25" diameter x 1" projection

CORD HUNG



- Currently offer 12 CSA-listed cord options for damp locations and 10 non-CSA listed cords for dry locations
- Customers receive 8 feet of standard cord and 6 feet of cotton cord with their fixture
- Ceiling canopy dimensions: 4.25" diameter x 1" projection

GOOSENECK



- Barn Light offers 27 gooseneck arm styles including 6 straight arm styles
- The five top-selling gooseneck arms are: G22, G15, G11, G26 and G1
- The wall backing plate measures 4.75" in diameter and is included with the purchase of any gooseneck light
- Also available are decorative backing plate covers and heavy duty backing plates (see page 2)

WALL SCONCE



- Barn Light offers a vast line of sconces including barn, rustic, vintage and modern styles
- Sconce shade sizes vary and range between the 6" Bowie Wall Sconce to the 14" Original™ Wall Sconce
- The wall backing plate measures 6.25" in diameter and is CSA listed for wet locations
- Several sconces are available with plug-in option which includes 8 ft. of cord and an inline switch

POST MOUNT



- Shade sizes offered include: 14", 15", 16" and 17"
- We offer six primary post mount styles: industrial guard, single, single decorative, double, double decorative and 3-light decorative. Post mounts are available in three finish colors (galvanized, black and white) while the shades are available in all standard powder coat and porcelain color options (see below)
- All post mount styles offer an optional 8', 10' or 12' direct burial pole with smooth or fluted

**FINISH OPTIONS:**

PORCELAIN ENAMEL



- The porcelain enamel process utilizes historic manufacturing techniques from the early 20th century
- Handcrafted from commercial grade steel providing a heavy-duty feel, glass-hard surface and brilliant sheen
- Barn Light currently offers 11 different porcelain enamel finish colors
- To create the porcelain enamel finish, shades are treated with multiple layers of porcelain enamel glass then fired in a high-temperature oven to form a bond between the enamel and steel shade
- Porcelain enamel fixtures are easy to maintain with a mild soap-and-water cleanup
- Please advise customers that all porcelain enamel fixtures have a black ring on the bottom ridge (see photo to the left) and underside of the shade will be white

POWDER COAT



- We currently offer 19 powder coat finish colors
- Galvanized steel shades are completed with a stylish textured finish to replicate a timeless industrial look
- Powder coat finishes do not have a black ring on the bottom ridge of the fixture. All porcelain enamel finish colors have a corresponding option in powder coat called paint-to-match porcelain finish
- Powder coat options 105-Textured Black, 605-Rust and 805-Charcoal Granite are matte, textured finishes
- The underside of a powder coat-finished shade will be white

NATURAL FINISHES



- We offer five natural finish options: raw brass, weathered brass, raw copper, oil-rubbed copper and weathered copper
- Without consistent cleaning, both brass and copper will develop a natural patina
- We recommend Brasso or Bar Keeper's Friend to properly clean natural finish fixtures

## GUARD & GLASS OPTIONS:



We offer three kinds of guards to enclose our glass jelly jars: a wire guard (WGG), regular cast guard (CGG) and heavy-duty cast guard (TGG)



We offer 6 different kinds of glass jelly jars and replacement jars can also be purchased through the website

## OPTIONAL FIXTURE ACCESSORIES:

### WIRE CAGE



- Available in the following sizes: 8", 10", 11", 12", 13", 14", 15", 16", 17", 18" and 20"
- Available in 20 different powder coat finish colors
- Adds an industrial flair to any shade and provides protection for the fixture's light bulb

### HANG STRAIGHT CANOPY



- This indoor only accessory features a ball and socket affixed to a backing plate that allows stem mount pendants to be mounted on sloped, vaulted and pitched ceilings
- Available with two stem connections: 1/2 inch receiver and 3/4 inch receiver
- Can be finished in all powder coat and PTMP powder coat colors

### HEAVY DUTY STEM MOUNT CANOPY



- A rugged and sturdy canopy that can handle any stem mount light with ease
- Available in two stem connections: 1/2 inch receiver and 3/4 inch receiver
- Suitable for indoor or outdoor locations and available in 15 powder coat finish colors

### DECORATIVE BACKING PLATE



- Made of solid cast aluminum and designed to dress up standard gooseneck backing plates
- Available with two backplate openings: 1/2 inch and 3/4 inch and suitable for indoor or outdoor locations
- Projection from wall is 2.5", 5" diameter
- Available in 15 powder coat finish colors as well as brass, copper and galvanized

### HEAVY DUTY SQUARE BACKING PLATE



- Made of solid aluminum and designed to provide the sturdiest foundation for any gooseneck light
- Available with two backplate openings: 1/2 inch and 3/4 inch
- Square measures 8" x 8"
- Suitable for indoor or outdoor locations and available in 16 powder coat finish colors

### DUSK-TO-DAWN PHOTOCELL



- A decorative backing plate for outdoor fixtures that contains a light sensor to automatically turn the light on at dusk and off at dawn
- Available in all powder coat and PTMP powder coat finish colors
- Max wattage is 200W standard incandescent

## LIGHT SOURCE OPTIONS:

All published luminaire photometric testing performed to IESNA LM-79-08 standards by a NVLAP accredited laboratory. Data is considered to be representative of the configurations shown, within the tolerances allowed by Lighting Facts. To obtain an IES file specific to your customer's project, please contact us.

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
<b>LED</b>					
LED11	11W	850	>90	120 VAC	TRIAC
LED16	16W	1250	>90	120-277 VAC	TRIAC
LED27	27W	2000	>90	120-277 VAC	0-10V
LED38	38W	3000	>90	120-277 VAC	0-10V
LED43	43W	4000	>90	120-277 VAC	0-10V
<b>INCANDESCENT (MED E26)</b>					
E26	200W MAX	1400	100	120 VAC	BULB DEPENDANT
<b>COMPACT FLOURESCENT (GU24 CFL)</b>					
GU24	23W MAX	1400	75	120 VAC	BULB DEPENDANT

### LED MODULE SPECIFICATION:

COLOR RENDERING INDEX: >90 CRI  
AVAILABLE CCT: 2700K, 3500K, 4000K

LUMEN MAINTENANCE (L70): 50,000 HOURS