

LIGHT SOURCE

All published luminaire photometric testing performed to IESNA LM-79-08 standards by a NVLAP accredited laboratory. Data is considered to be representative of the configurations shown, within the tolerances allowed by Lighting Facts. To obtain an IES file specific to your project, please contact the factory.

OPTION	WATTAGE	LUMENS <small>*Avg. value, actual value dependent on bulb used</small>	CRI	VOLTAGE	DIMMING
INCANDESCENT (MED E26)					
E26	60W Max	1400*	100	120 VAC	Bulb Dependant

SPECIFICATIONS

MOUNTING & FINISHES

CANOPY
5" Hand-Spun, High Purity 0.050" Thick 3003-O Temper Aluminum Canopy

CORD
Cord-hung Pendants Include 7' Of Standard Cord Or 5' Of Cotton Cord, +/- For Socket Orientation

POWDER COAT FINISHES
Polyester Powdercoat Electro-Staticly Applied and Thermocured to Canopy

CERTIFICATIONS, LISTINGS & WARRANTY

MADE IN THE USA
Manufactured and Hand-Crafted in Titusville, FL

CSA LISTED FOR DAMP OR DRY LOCATIONS
Dependent on Cord Selection

LIMITED WARRANTY
For Additional Information on our Limited Warranty, Please See our Terms & Conditions

LIGHT SOURCE

SOCKET
E26 Medium Base Socket, 60W Max