

INDUSTRIAL STATIC TOPLESS RING SCONCE



JOB NAME: FIXTURE TYPE:

BLE - W - RGU -	-	-		
-	Α	В	С	

DEL W NGO	Α	В	С
Order Example: BLE - W	V - RGU - 300 - RIB - E26		

A - FINISHES

POWDER COAT FINISHES:

100 Black

105 **Textured Black**

106 Matte Black 200 White

206 Matte White 300 Dark Green

307 **Emerald Green**

311 Jadite

370 Mint

Chartreuse 380

390 Teal 400 Barn Red

420 Orange

470 Watermelon

480 Blush Pink

490 Magenta

495 **Sherbet Orange** 500 **Buttery Yellow**

570 Sunflower

600 Bronze

601 Chocolate

605 Rust

615 Oil-Rubbed Bronze

700 Royal Blue

705 Navy

710 **Cobalt Blue**

715 Delphite Blue

790 Lavender

800 Industrial Grey

A - FINISHES (CONT'D.)

POWDER COAT FINISHES:

805 **Charcoal Granite**

810 Graphite

975 Galvanized

B - GLASS OPTIONS

CLR Clear Glass **FST** Frosted Glass RIB **Ribbed Glass** BLU Blue Glass **RED Red Glass**

Amber Glass **AMB**

GRN Green Glass


C - SOCKET TYPE


E26 100 Watt Max

GU24 24 Bi-Pin, 18 Watt Max¹

IMPORTANT: (1) Fixtures configured with a GU24 socket are non-returnable

MOUNTING DIMENSIONS





SPECIFICATIONS

CERTIFICATIONS, LISTINGS & WARRANTY

MADE IN THE USA

Manufactured and Hand-Crafted in Our 60,000 Square Foot Facility Located in Titusville, FL

CSA LISTED FOR WET LOCATIONS

Only When Mounted Vertically

LIMITED WARRANTY

For Additional Information on Our Limited Warranty, Please See Our Terms & Conditions

CONSTRUCTION & FINISH

STATIC RINGS

Constructed of 6061-T6 Aluminum

POWDER COAT FINISHES

Polyester Powder Coat Finishes Are Electro-Statically Applied and Thermocured on Fixture and Backing Plate

LIGHT SOURCE

INCANDESCENT

Medium Base E26 Socket, 120 VAC, 100 Watt Max

COMPACT FLUORESCENT

Bi-Pin Base GU24 Socket, 120 VAC, 18 Watt Max