



Item #	Diameter (A)	Height (B)
ULW12-PC	12"	12"
ULW14-PC	14"	13 ½"
ULW16-PC	16"	15"
ULW18-PC	18"	16 ¼"


ULW12-PC




ULW14-PC



ULW16-PC



ULW18-PC



Model #	Item #	Standard Finishes	Mounting Options	Mounting Color	Optional Accessories	Accessory Colors	Wattage/Lamp Options	Ballast	Voltage
C- Cord Hung S- Stem Mount G- Goose-Neck F- Flush Mount CN- Chain Hung	ULW12-PC ULW14-PC ULW16-PC ULW18-PC	<i>Powder Coat:</i> 100 -Black 200 -White 300 -Dark Green 600 -Bronze 605 - Rust <i>Other:</i> 975 - Galvanized <i>For additional colors, see color chart</i>	<i>Cord:</i> Standard ¹ : SBK Black SWH White Cotton ² : CRZ Red Chevron CGM Grey CBK Black Cotton Twists ² : TBR Brown TBK Black TPT Putty <i>Stem:</i> ST _____ ^Specify stem model <i>Gooseneck:</i> G _____ ^Specify gooseneck model <i>Flush Mount:</i> FM <i>Chain Hung</i> ³ : CN Standard length is 3 ft. <i>For additional mounting options and details, see mounting option chart</i>	Standard Finish for ALL Mounting is: Same as fixture // Leave Code Blank OR <i>Cord:</i> Canopy color: 100 - Black 200 -White <i>Stem and Gooseneck :</i> 100 - Black 200 - White 975 - Galvanized 980 - Brushed Aluminum <i>Chain:</i> Chain & Canopy color: 100 - Black 200 - White 975 - Galvanized <i>For additional colors, see color chart</i>	WC -Wire Cage HSC -Hang Straight Canopy HDSM - Heavy Duty Stem Mount Canopy HDBP - Heavy Duty Backing Plate	Standard Finish for Accessories is: Same as fixture // Leave Code Blank OR <i>Powder Coat:</i> 100 -Black 400 -Barn Red 975 -Galvanized <i>For additional colors, see color chart</i>	200 Watt maximum GU-24 Bi-Pin (Max 23 watt per socket)		120V
BLE-C	ULW16-PC	100	SBK			100			

ORDER SPECIFICS

BLE-	-PC								
------	-----	--	--	--	--	--	--	--	--

¹ Suitable for Damp locations. Standard length 8 feet. ² Suitable for Dry locations Only (Not CSA listed). Standard length 6 feet. ³ Standard length is 3ft. *Additional lengths available on Cord, Stem & Chain