

Item #	Diameter (A)	Height (B)
WHA12-PC	12"	6 ¾"
WHA14-PC	14"	7 ¾"
WHA16-PC	16"	8 ½"

Model #	Item #	Standard Finishes	Mounting Options	Mounting Color	Optional Accessories	Accessory Colors	Wattage/Lamp Options	Ballast	Voltage
C- Cord Hung S- Stem Mount G- Goose-Neck F- Flush Mount CN- Chain Hung	WHA12-PC WHA14-PC WHA16-PC	Powder Coat: 100 -Black 200 -White 300 -Dark Green 600 -Bronze 605 - Rust <i>Other:</i> 975 - Galvanized <i>For additional colors, see color chart</i>	Cord: Standard ¹ : SBK Black SWH White Cotton ² : CRZ Red Chevron CGM Grey CBK Black Cotton Twists ² : TBR Brown TBK Black TPT Putty Stem: ST _____ ^Specify stem model Gooseneck: G _____ ^Specify gooseneck model Flush Mount: FM Chain Hung ³ : CN Standard length is 3 ft. <i>For additional mounting options and details, see mounting option chart</i>	Standard Finish for ALL Mounting is: Same as fixture // Leave Code Blank OR Cord: Canopy color: 100 - Black 200 -White Stem and Gooseneck : 100 - Black 200 - White 975 - Galvanized 980 - Brushed Aluminum Chain : Chain & Canopy color: 100 - Black 200 - White 975 - Galvanized <i>For additional colors, see color chart</i>	CGG - Cast Guard and Glass ⁴ WGG - Wire Guard and Glass ⁴ TGG - Heavy Duty Cast Guard and Glass ⁴ WC -Wire Cage HSC -Hang Straight Canopy HDSM - Heavy Duty Stem Mount Canopy HDBP - Heavy Duty Backing Plate	Standard Finish for Accessories is: Same as fixture // Leave Code Blank OR Powder Coat: 100 -Black 400 -Barn Red 975 -Galvanized <i>For additional colors, see color chart</i> Vapor Proof Glass ⁴ : CLR - Clear FST - Frosted RIB - Ribbed <i>For additional glass options, see guard and glass chart</i>	200 Watt maximum GU-24 Bi-Pin (Max 23 watt per socket)		120V
BLE-C	WHA16-PC	100	SBK		CGG	100-FST			
ORDER SPECIFICS									
BLE-	-PC								

Notes:

¹ Suitable for Damp locations. Standard length 8 feet. ² Suitable for Dry locations Only (Not CSA listed). Standard length 6 feet. ³ Standard length is 3ft. *Additional lengths available on Cord, Stem & Chain

⁴ Guard/Glass options reduce wattage to 100W & GU-24 Bi-Pin to 18W. **Suitable for Wet Location (except when cord mounted)**