

SWITCH OPTIONS

A functional on/off turnkey or paddle switch contributes practicality and authentic details to the Fargo’s aesthetic. The socket and switch will receive the same finish color as the mounting, selected in Section B.



NS NONE/NO SWITCH



TKS TURN KEY SWITCH



PS PADDLE SWITCH

LIGHT SOURCE

All published luminaire photometric testing performed to IESNA LM-79-08 standards by a NVLAP accredited laboratory. Data is considered to be representative of the configurations shown, within the tolerances allowed by Lighting Facts. To obtain an IES file specific to your project, please contact the factory.

OPTION	WATTAGE	LUMENS <small>*Avg. value, actual value dependent on bulb used</small>	CRI	VOLTAGE	DIMMING
INCANDESCENT (MED E26)					
E26	60W Max	1400*	100	120 VAC	Bulb Dependant

SPECIFICATIONS

CONSTRUCTION

BACKING PLATE
Crafted From High Purity 0.050” Thick 3003-O Temper Aluminum

MOUNTING ARM
Manufactured from 3/8” Diameter Brass/Aluminum Tubing

SHADE & FINISHES

FARGO SHADE
Hand-Spun, High Purity 0.050” Thick 3003-O Temper Aluminum Shade

POWDER COAT FINISHES
Polyester Powdercoat Electro-Statically Applied and Thermocured

LIGHT SOURCE

SOCKET
E26 Medium Base Socket, 60W Max

CERTIFICATIONS, LISTINGS & WARRANTY

MADE IN THE USA
Manufactured and Hand-Crafted in Titusville, FL.

CSA LISTED FOR DRY LOCATIONS

LIMITED WARRANTY
For Additional Information on our Limited Warranty, Please See our Terms & Conditions