



**LIGHT SOURCE**

All published luminaire photometric testing performed to IESNA LM-79-08 standards by a NVLAP accredited laboratory. Data is considered to be representative of the configurations shown, within the tolerances allowed by Lighting Facts. To obtain an IES file specific to your project, please contact the factory.

OPTION	WATTAGE	LUMENS	CRI	VOLTAGE	DIMMING
<b>LEDS</b>					
<b>LED11</b>	11W	850	>90	120 VAC	TRIAC
<b>LED16</b>	16W	1250	>90	120 VAC	TRIAC

**SPECIFICATIONS**

**MOUNTING**

**CANOPY**  
6" Hand-Spun, High Purity 0.050" Thick 3003-O Temper Aluminum Canopy

**CORD**  
Cord-hung Pendants Include 7' Of Standard Cord Or 5' Of Cotton Cord, +/- For Socket Orientation

**SHADE & FINISHES**

**COLBY SHADE**  
Hand-Spun from High Purity 0.050" Thick 3003-O Temper Aluminum

**POWDER COAT FINISHES**  
Polyester Powder Coat Finishes Are Electro-Statically Applied and Thermocured

**LED SPECIFICATIONS**

**LUMEN MAINTENANCE**  
L90(6K) > 36,300 Hours

**COLOR TEMPERATURES**  
Standard Color Temperatures Available Include 2700K, 3000K, 3500K and 4000K. Custom Temperatures Available upon Request.

**CRI**  
Minimum 90 CRI. Consult Factory for Other CRI Options.

**EFFICACY**  
Up to 100 LPW Based on Wattage/Lumens in the Table

**DRIVER & DIMMING OPTION**  
850 and 1250 Lumen, Reliant on Triac Dimming 12w / 120v Mounted in Canopy, up to 5% Dimming.

**CERTIFICATIONS, LISTINGS & WARRANTY**

**MADE IN THE USA**  
Manufactured and Hand-Crafted in Our 60,000 Square Foot Facility Located in Titusville, FL

**CSA LISTED FOR DAMP LOCATIONS**

**LIMITED WARRANTY**  
For Additional Information on Our Limited Warranty, Please See Our Terms & Conditions