



PROJECT TYPE \_\_\_\_\_

BLE - BALL - MASON - \_\_\_\_\_ - \_\_\_\_\_  
A B

<b>100</b>	Black
<b>200</b>	White
<b>975</b>	Galvanized

**LIGHT SOURCE**

All published luminaire photometric testing performed to IESNA LM-79-08 standards by a NVLAP accredited laboratory. Data is considered to be representative of the configurations shown, within the tolerances allowed by Lighting Facts. To obtain an IES file specific to your project, please contact the factory.

OPTION	WATTAGE	CRI	VOLTAGE	DIMMING
INCANDESCENT (MED E26)				
E26	60W Max	100	120 VAC	Bulb Dependent

**SPECIFICATIONS****DESIGN**

## CANOPY

Hand-Spun, High Purity 0.050" Thick 3003-O Temper Aluminum Canopy

## CORD

Cord-hung Pendants Include 7' Of Standard Cord Or 5' Of Cotton Cord, +/- For Socket Orientation

**FINISHES**

## POWDER COAT FINISHES

Polyester Powder Coat Finishes Are Electro-Statically Applied and Thermocured on the Canopy

**CERTIFICATIONS, LISTINGS & WARRANTY**

## MADE IN THE USA

Manufactured and Hand-Crafted in Our 60,000 Square Foot Facility Located in Titusville, FL

## CSA LISTED FOR DRY LOCATIONS

## LIMITED WARRANTY

For Additional Information on Our Limited Warranty, Please See Our Terms & Conditions