




SPS-0506 REV C

**LOMA LED SERIES**

JOB NAME: \_\_\_\_\_ FIXTURE TYPE: \_\_\_\_\_



BLE - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_

A                      B                      C                      D                      E                      F                      G

\_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_

H                      I                      J

Order Example: BLE - CN - DBL20 - 100 - 200 - CN72 - 100 - CSBW - LED43 - 3000K - DL

**A - MOUNTING STYLE**

- C** Cord Hung  
**S** Stem Mount  
**CN** Chain Hung

**B - SHADE & SHADE SIZE****LOMA:**

- DBL12** 12" Shade  
**DBL16** 16" Shade  
**DBL20'** 20" Shade

**C - EXTERIOR SHADE FINISH****PORCELAIN FINISHES:**

- 150** Black  
**250** White  
**350** Vintage Green  
**355** Jadite  
**455** Cherry Red  
**550** Yellow  
**650** Bronze  
**750** Cobalt Blue  
**765** Delphite Blue  
**850** Graphite  
**950** Metallic Chrome

**POWDER COAT FINISHES:**

- 100** Black  
**105** Textured Black  
**200** White  
**300** Dark Green  
**307** Emerald Green  
**311** Jadite  
**370** Mint  
**380** Chartreuse  
**390** Teal  
**400** Barn Red  
**420** Orange  
**470** Watermelon  
**480** Blush Pink  
**490** Magenta  
**495** Sherbet Orange  
**500** Buttery Yellow  
**570** Sunflower  
**600** Bronze  
**601** Chocolate  
**605** Rust  
**615** Oil-Rubbed Bronze  
**700** Royal Blue  
**705** Navy  
**710** Cobalt Blue  
**715** Delphite Blue  
**790** Lavender  
**800** Industrial Grey  
**805** Charcoal Granite

**C - EXTERIOR SHADE FINISH (CONTINUED)****POWDER COAT FINISHES:**

- 810** Granite  
**930** Painted Aged Brass  
**940** Painted Aged Copper  
**975** Galvanized

**D - INTERIOR SHADE FINISH<sup>3</sup>****POWDER COAT FINISHES:**

- 100** Black  
**105** Textured Black  
**200** White  
**300** Dark Green  
**307** Emerald Green  
**311** Jadite  
**370** Mint  
**380** Chartreuse  
**390** Teal  
**400** Barn Red  
**420** Orange  
**470** Watermelon  
**480** Blush Pink  
**490** Magenta  
**500** Buttery Yellow  
**570** Sunflower  
**600** Bronze  
**601** Chocolate  
**605** Rust  
**615** Oil-Rubbed Bronze  
**700** Royal Blue  
**705** Navy  
**710** Cobalt Blue  
**715** Delphite Blue  
**800** Industrial Grey  
**805** Charcoal Granite  
**810** Graphite  
**930** Painted Aged Brass  
**940** Painted Aged Copper  
**975** Galvanized

**E - MOUNTING****CSA LISTED CORD OPTIONS:**

- SBK** Standard Black  
**SWH** Standard White  
**CSB** Black Cloth  
**CSW** White Cloth  
**CMG** Grey Cloth  
**CSR** Red Cloth  
**CRZ** Red Chevron Cloth  
**CSBW** Black & White Cloth  
**CSRW** Red & White Cloth  
**CSBG** Black & Gold Cloth  
**CSBP** Black & Pink Cloth

**E - MOUNTING (CONTINUED)****CSA LISTED CORD OPTIONS:**

- CSGW** Gold & White Cloth  
**CSUW** Blue & White Cloth  
**CSBB** Black & Brown Cloth

**STEM MOUNT OPTIONS:**

- ST506** .5" Stem Mount, 6"  
**ST512** .5" Stem Mount, 12"  
**ST518** .5" Stem Mount, 18"  
**ST524** .5" Stem Mount, 24"  
**ST536** .5" Stem Mount, 36"  
**ST548** .5" Stem Mount, 48"  
**ST706** .75" Stem Mount, 6"  
**ST712** .75" Stem Mount, 12"  
**ST718** .75" Stem Mount, 18"  
**ST724** .75" Stem Mount, 24"  
**ST736** .75" Stem Mount, 36"  
**ST748** .75" Stem Mount, 48"

**CHAIN MOUNT OPTIONS:**

- CN36** 3' of Chain  
**CN48** 4' of Chain  
**CN60** 5' of Chain  
**CN72** 6' of Chain

**F - MOUNTING FINISH**

Please Note: See **Section C** for all applicable Mounting Finish options. Additionally, 980-Brushed Aluminum is available.

(I) If Cord Hung [C] Mounting Style, selection identifies canopy finish.

(II) If Stem Mount [S] Mounting Style, selection identifies stem and canopy finish.

(III) If Chain Hung [CN] Mounting Style, selection identifies chain and canopy finish.

- 980** Brushed Aluminum<sup>4</sup>

**G - CORDS<sup>2</sup>**

Please Note: See **Section E** for all applicable CSA Listed Cord Options for Chain Hung Mounting Style

- NA** Not Applicable

**H - LIGHT SOURCE**

- LED11** 850 Lumen, 11W LED  
**LED16** 1250 Lumen, 16W LED  
**LED27** 2000 Lumen, 27W LED  
**LED38** 3000 Lumen, 38W LED  
**LED43** 4000 Lumen, 43W LED

**I - COLOR TEMPERATURE**

- 2700K** Warm White/Soft White  
**3000K** Neutral White  
**3500K** Bright White  
**4000K** Cool White


**J - LED LENS**

- DL** Domed Lens  
**FL** Flat Lens

**IMPORTANT:** (1) Not available in Porcelain Finishes (2) Only applicable if Chain Hung Mounting Style selected in Section A, select NA if another Mounting Style is selected (3) Not applicable if Porcelain Enamel finish is selected in Section C. If Porcelain Enamel finish selected, interior shade finish will be white. (4) Only applicable if Stem Mount is selected in Section A


**MOUNTING STYLE**

**ALTERNATE CANOPY DESIGN**




Required if LED 27, 38, 43 Light Source selected in Section H


**CORD HUNG PENDANT (C)**




**STEM MOUNT PENDANT (S)**



**CHAIN HUNG PENDANT (CN)**



**LUMINAIRE DIMENSIONS**



SHADE CODE	HEIGHT (A)	DIAMETER (B)
DBL12	6"	12"
DBL16	8"	16"
DBL20	10"	20"

**SPECIFICATIONS**

**LED 11, 16, 27, 38, 43 LIGHT SOURCE**

LED TYPE: CREE LMH2 MODULE  
 INITIAL LUMENS DELIVERED: UP TO 4000 LUMENS  
 L90(6K) > 36,300 HOURS  
 AVAILABLE CCT: 2700K, 3000K, 3500K, 4000K  
**Custom Temperatures Available upon Request**  
 90+ CRI  
 2 STEP MACADAMS ELLIPSE  
 EFFICACY: UP TO 93 LPW  
**High Efficacy Available upon Request, Consult Factory for Additional Information**

**DIMMING**

LED 11 & 16  
 Triac Dimming at 100-120VAC, Able to Dim down to 5%.  
 Dependent on Specific Dimmer.  
 0-10V & ELV Dimming Available upon Request.  
 LED 27, 38 & 43  
 0-10V Dimming, Able to Dim down to 10%.  
 Dependent on Specific Dimmer.  
 Triac & ELV Dimming Available upon Request.  
 TRIAC DIMMING AT 230 VAC  
 Available by Request for LED 11 and 16  
 COMPATIBLE DIMMERS  
 Consult Factory for Additional Information on Dimming

**CONSTRUCTION & FINISHES**

PORCELAIN SHADE  
 Hand-Spun from 20 Gauge Sheet Metal  
 PORCELAIN FINISHES  
 Applied by Hand and Fired in a High Temperature Oven  
 POWDER COAT FINISHES  
 Polyester Powder Coat Finishes Are Electro-Statically Applied and Thermocured  
 POWDER COAT SHADE  
 Hand-Spun from High Purity 0.050" Thick 3003-O Temper Aluminum  
 MAX FIXTURE WEIGHT  
 15 lbs

**CERTIFICATIONS, LISTINGS & WARRANTY**

MADE IN THE USA  
 Manufactured and Hand-Crafted in Our 60,000 Square Foot Facility Located in Titusville, FL  
 CSA LISTED FOR WET LOCATIONS  
 Includes All Stem Mounting Styles  
 CSA LISTED FOR DAMP LOCATIONS  
 Includes All Chain and Cord Hung Mounting Styles  
 LIMITED WARRANTY  
 For Additional Information on Our Limited Warranty, Please See Our Terms & Conditions

**LED 11, 16 ELECTRICAL/LED DRIVER**

DRIVER TYPE: LMD125  
 DRIVE CURRENT: 440mA  
 POWER FACTOR > 0.9  
 EFFICIENCY: UP TO 81% TYPICAL  
 INPUT VOLTAGE: 100-120 VAC (SEE DIMMING SECTION)  
 CLASS 2 POWER SUPPLY  
 LED DRIVER LIFETIME: > 50,000 HOURS (@ 25 DEG C AMBIENT)  
 CONDUCTED AND RADIATED EMI  
 Compliant with FCC CFR Title 47 Part 15 Class B (120 VAC), Class A (277 VAC) and EN55015 (CISPR 15) at 230 VAC

**LED 27, 38, 43 ELECTRICAL/LED DRIVER**

DRIVER TYPE: LMD400  
 DRIVE CURRENT: 940mA  
 POWER FACTOR > 0.95  
 EFFICIENCY: UP TO 81% TYPICAL  
 INPUT VOLTAGE: 120-277 VAC (SEE DIMMING SECTION)  
 CLASS 2 POWER SUPPLY  
 LED DRIVER LIFETIME: > 50,000 HOURS (@ 25 DEG C AMBIENT)  
 CONDUCTED AND RADIATED EMI  
 Compliant with FCC CFR Title 47 Part 15 Class B (120 VAC), Class A (277 VAC) and EN55015 (CISPR 15) at 230 VAC

**MOUNTING**

STEM  
 1/2" Nominal (0.84" Actual) or 3/4" Nominal (1.05" Actual) Sch 40, 6063 Aluminum Mounting Stem. Custom Lengths Available upon Request.  
 CORD  
 Cord-Hung Pendants Include 7' of Standard Cord or 5' of Cloth Cord, +/- For Socket Orientation  
 CHAIN  
 4-Gauge Chain Complete with Quick Link for On-Site Adjustments to Chain's Length